

## PROBAU All Weather Sealant 310 ml

Elastic sealing compound with a synthetic rubber base. Ready to use.

### Type of use:

PROBAU All Weather Sealant is suitable for repairing and sealing holes and cracks in roof and façade areas, e.g.: gutters, dormer windows, rooflights, chimneys and bitumen roof membranes. Bonds to bitumen surfaces, glass, metal and concrete without the need for a primer coat. For outdoor applications only.

### Application:

Read the safety guidelines before commencing work. If necessary, cover the edges of the joint with masking tape. Screw on the cartridge nozzle and cut off the end of the nozzle at an angle according to the required joint width. Apply the PROBAU All Weather Sealant uniformly in the joint with a suitable cartridge gun. Before a skin forms, use a smoothing agent and suitable smoothing tool to smooth the sealant. Remove the masking tape immediately after smoothing the joint.

### Subsurface:

Suitable subsurfaces are clean, solid, load-bearing surfaces and slightly damp surfaces. PROBAU All Weather Sealant bonds to almost all materials, such as bitumen membranes, concrete, fibre-cement panels, stone, plaster, glass, metal and many plastics. In extreme conditions and on certain plastics, we recommend applying a silicone primer first. If the joints are deep, fill them first with suitable non-absorbent foam backing material (PE backer rod).

### Note:

Only use for installation outdoors!  
Dries physically. (Evaporation of solvents)  
Contains flammable solvents.



## **PROBAU All Weather Sealant 310 ml**

The times indicated for skin formation and hardening are affected by storage and can change as the product ages.

### **Quantity required:**

Sufficient for creating a joint that is approximately 8 to 9 m long (with a joint width of 6 mm and depth of 6 mm).

### **Processing and curing times and temperatures:**

+5 °C to +40 °C (optimally +5 °C to +20 °C). Hardening time: approximately 2 mm per day.

### **Temperature resistance:**

Approximately -25 °C to +100 °C

### **Admissible total deformation:**

Maximum 25%

### **Storage:**

Store in cool, dry, frost-free conditions.

### **Shelf life:**

In its unopened original packaging, the product has a shelf life of 24 months from its date of manufacture. See the date stamp.

### **Container:**

310ml cartridge

### **Colours:**

Transparent, aluminium

## **PROBAU All Weather Sealant 310 ml**

### **Disposal:**

Only send completely empty packaging for recycling. Leftover material can be disposed of at your local disposal centre for problem waste.

### **Constituents:**

A safety data sheet is available on enquiry.

### **Precautionary statements:**

Keep out of the reach of children. Contains n-Butyl acetate. The liquid and the vapour are flammable! Can cause drowsiness and dizziness. Repeated contact can result in rough or cracked skin. Keep the product away from hot surfaces, sparks, open flames and other sources of ignition. No smoking. Keep the container tightly sealed. Store in a well-ventilated place. Keep cool. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. A safety data sheet is available on enquiry.

The details provided in this information sheet are based on intensive application tests in the laboratory and in practice and are intended as guideline values. The responsibility for using the material in each case lies with the person using it. The guideline values do not represent any guarantee or assurance.